



POWER PRODUCT

Tractor Hydrostatic

ConTRAC 26



Technology
at your service

D E V E L O P A N D F U N C T I O N A L I T Y

ConTRAC 26

Engine	Yanmar 3TNV82 - Kw (HP) 19.0 (25.8)
Tank Capacity	22 l
Consumo combustibile	4,40 l/h - 3600 rpm
Gear box	3 speeds - (0/7; 0/14; 0/28 km/h)
Power take off	mechanical transmission rear 1-3/8" (540 rpm) clockwise rotation front 1-3/8" (2000 rpm) clockwise rotation
Front power lift	hydraulic with 3 functions
Capacity	350 kg.
Power lift system	triangle Cat. 0
Rear power lift	hydraulic
Capacity	450 kg.
Command system	floating control position with blocking device for transport
Power lift system	3 point linkage (standard) Cat. IN
Differential	locking device on the rear axle
Transmission	hydrostatic
Brakes	multidisc in oil bath on the fast axle
Traction	four wheel drive with disengagement
Front axle	floating
Rear axle	portal system
Safety device	"PUSH AND START" safety device on the clutch pedal
Overall width	1230
Turning radius - external	(2WD 275) (4WD 310)
Turning radius - internal	(2WD 106) (4WD 157)
Wheelbase	1515
Tires	320/60-15 - 20x8.00-10
Weight (Standard/Cab)	1023/1133 Kg.

I	0 ÷ 7	0 ÷ 3	RM
II	0 ÷ 14	0 ÷ 7	RM
III	0 ÷ 28	0 ÷ 14	RM

Tiller (rpm) with tires 320/60-15 - 20x8.00-10

TURNING RADIUS (m) :	2,55
WEIGHT (Kg.)	870
WEIGHT WITH CABIN	980
MAXIMUM PERMISSIBLE LOAD (Kg)	
Front axle:	650
Rear axle:	1.000
TOTAL:	1.450
MEASURES OF DIMENSIONS (mm)	
Length	2.300
Length with lift:	2.810
Length:	1.225
Height:	1.410
Height with cab:	2.010
STEP	1.350
Track front	930
Track rear	910



BARBIERI s.r.l

Via Seccalegno, 23 - 36040 SOSSANO (VI) ITALY
Tel.: +39 - 0444 - 885 722
Fax: +39 - 0444 - 885 482
www.barbierisrl.com - e-mail info@barbieri-fb.com